

M Series Small Size Touch Monitor

True Flat Touch Monitor



Features and Benefits

- ◆ Support Resistive Touch
- ◆ USB or VGA Interface Available
- ◆ Optional Die-Casting Aluminum Base
- ◆ Easy for Installation - One USB Cable Needed
- ◆ Best Choice for Space Limited Retail / Hospitality Settings
- ◆ Spill Proof and Anti-Dust



M Series Small Size Touch Monitor

OTEK_{SYS}



USB Interface Available



VGA Interface Available



75 x 75m VESA Wall Mount



Optional Die-Casting Stand

Specification

MODEL NAME	M354RD	M354RC	M365RD	M365RC
Display Size	8"		10.4"	
Optimal Resolution	800 * 600		800 * 600	
Panel Brightnes	350 cd/m ² (typ)		250 cd/m ² (typ)	
Contrast Ratio	500:1 (typ)		500:1 (typ)	
Response Time	25 ms (typ)		20 ms (typ)	
Viewing Angle(L / R / U / D)	70 / 70 / 50 / 70		70 / 70 / 50 / 60	
Tilt Angle	N/A		N/A	
Input Video signal	DIN	USB B Type	DIN	USB B Type
Touch	Resistive Touch, USB interface			
Power consumption	6W	2.5W	8W	2.5W
Input Frequency	Horizontal: 31.5-60.2 kHz ; Vertical :56.3Hz~75Hz			
Power supply	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%
Temperature	Operating : 0°C~40°C ; Storage : -10°C~50°C			
Humidity	Operating : 20%~80% ; Storage : 10%~90%			
Weight	0.8Kgs (1.76lbs)		1.1Kgs (2.42lbs)	
Physical Dimension WxHxD	202*163*34.5(mm)	79.5*64.2*13.6(inch)	244*197*36(mm)	96.1*77.6*14.2(inch)
Optional	White, Wall Mount Kit , Stand			

* This specification is subject to change without prior notice.

OTEK SYSTEM CO., LTD.

Address: 6F., No.30, Singjhong Rd., Neihu District, Taipei, Taiwan Tel: +886-2-7720-1688 Fax: +886-2-7721-2188

http://www.oteksys.com E-mail:sales@oteksys.com

