

PS-3316E

POSIFLEX

Slim and Flexible

Streamlined design equips with a foldable base; PS-3316E provides users with unmatched flexibility to adjust the screen to a height and angle depending on the application.

Expandable and Neat

Designed to better manage peripheral connectivity by separating a full set of ports into the top of the terminal, PS-3316E ensures neat, reliable peripheral cabling.

Specification	PS-3316E
Processor	Intel J1900 processor, 2.00GHz/2.42GHz (Burst), 2M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 8GB
Storage Device	1 x SATA, SATA SSD default
Power Supply	12V/40W
OS Support	Windows 10 IoT/Windows Embedded 8.1 Industry/Windows 7/POSReady 7/Linux per request

Display & Touch	
LCD Display	15.6" TFT LCD, Default: 1024 x 768, 1366 x 768 max.
Touch Function	5-wire resistive touch

Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	3 x DB9 + 1 x RJ45, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
UPS Port	N/A
Standard USB Port	5
PS/2 Port	1, via optional conversion cable
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
Audio	Buzzer only
WiFi	Optional internal USB WiFi module

Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	4.7

Environment	
Operation Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Options	
SA-105	Side Attachment with 3 track MSR
SA-205	Side Attachment with iButton
SA-305	Side Attachment with support for 3 track MSR, RFID and Fingerprint Sensor
SA-405	Side Attachment for with support for 3 track MSR, 3G dongle and Fingerprint Sensor
SA-505	3-in-1 attachment with MSR (default), RFID & iButton support
LM-6807U/LM-6810U	7" 800 x 480 / 10" 1024 x 768 rear-mount; 2 nd display (USB interface)
PD-2609UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-360UE/PD-360R	2 x 20 LCD, rear-mount, USB with Virtual COM support, (PD-360UE) / RS232(PD-360R)
PD-6807U	7" color LCD graphical line display, rear-mount (USB interface)
KP-500	40-key dynakey attachment with MSR or RFID option

* The product information and specifications are subject to change without prior notice.

U.S. Patent 9004436

Certifications



Design and Manufacturing in Taiwan by Posiflex Technology, Inc.

2016Q3

POSIFLEX

POSIFLEX TECHNOLOGY, INC.
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller

A Robust, Economic Choice



PS-3316E

Best Value Fanless POS Terminal

PS-3316E is a 15.6" wide touch screen fanless POS Terminal with all the essential function and capabilities to satisfy businesses of all sizes, and represent one of the best value choices in the entry-level POS Terminal segment.