

M Series Small Size Non-Touch Monitor

True Flat Display



Features and Benefits

- ◆ USB or VGA Interface Available
- ◆ Durable Die-Casting Aluminum Base for Option
- ◆ 7", 8" and 10" Pole Base for Option
- ◆ Easy for Installation - Only USB Cable Needed
- ◆ Spill Proof and Anti-Dust
- ◆ Best Choice for Space Limited Retail / Hospitality Settings
- ◆ True Flat Designed to Suit Harsh Environment



M363



M354



M365



M Series Small Size Non-Touch Monitor

OTEKsys



USB Interface Available



VGA Interface Available



True Flat Design



Wall Mount Available



Die-Casting Base for Option



7", 8" and 10" Pole Base for Option

Specification

| MODEL NAME | M363ND | M363NC | M354ND | M354NC | M365ND | M365NC |
|------------------------------|--|---------------|--|---------------|--|---------------|
| Display Size | 7" | | 8" | | 10.4" | |
| Optimal Resolution | 800 * 480 | | 800 * 600 | | 800 * 600 | |
| Panel Brightness | 350 cd/m ² (typ) | | 350 cd/m ² (typ) | | 350 cd/m ² (typ) | |
| Contrast Ratio | 500:1 (typ) | | 500:1 (typ) | | 500:1 (typ) | |
| Response Time | 25 ms (typ) | | 25 ms (typ) | | 20 ms (typ) | |
| Viewing Angle(L / R / U / D) | 70 / 70 / 50 / 70 | | 70 / 70 / 50 / 70 | | 70 / 70 / 50 / 60 | |
| Tilt Angle | 35°C(V) / 70°C(H) w/pole | | N/A | | N/A | |
| Input Video signal | DIN | USB B Type | DIN | USB B Type | DIN | USB B Type |
| Power consumption | 6W | 2.5W | 6W | 2.5W | 8W | 2.5W |
| Input Frequency | Horizontal: 31.5-60.2 kHz ; Vertical : 56.3Hz~75Hz | | | | | |
| Power supply | DC 12V +/- 10% | DC 5V +/- 10% | DC 12V +/- 10% | DC 5V +/- 10% | DC 12V +/- 10% | DC 5V +/- 10% |
| Temperature | Operating : 0°C~40°C(32 F ~ 104 F) ; Storage : -10°C~50°C (14 F ~ 122 F) | | | | | |
| Humidity | Operating : 20%~80% ; Storage : 10%~90% | | | | | |
| Weight | 0.5Kg (1.27lbs) | | 0.7Kg (1.78lbs) | | 0.85Kg (2.16lbs) | |
| Physical Dimension WxHxD | 184.5*118*34.5 (mm) 72.7*46.5*13.6 (inch) | | 202*163*34.5 (mm) 79.6*64.2*13.6 (inch) | | 244*197.4*36.4 (mm) 96.1*77.8*14.3 (inch) | |
| Optional | White, Wall Mount Kit | | | | | |

* This specification is subject to change without prior notice.

OTEK SYSTEM CO., LTD.

Address: 6F., No.30, Singjehong Rd., Neihu District, Taipei, Taiwan Tel: +886-2-7720-1688 Fax: +886-2-7721-2188

http://www.oteksys.com E-mail:sales@oteksys.com

