

TVS

PA Series

17" POS LCD Display

Product Features

- Fast Response Time
- Adjustable Tilt Stand Base
- VESA Wall Mount Support
- Clean Front View by Inherit Keys Design
- Touch combo interface



PA17

17" POS LCD Display

Function Panel



Feature



Card Reader Version



Touch Screen



Anti-Reflection Strengthen Glass





Touch Combo Interface

Specification

Specification \ Model		PA Series
		PA17
Panel	Viewing Area	17"
	Resolution	1280(H) x 1024(V) [SXGA]
	Color	16.7M
	Viewing Angle	Horizontal:170° & Vertical:160° (Typ.)
	Response Time Tr/Tf	2/3 ms (Typ.)
	Contrast Ratio	1000:1 (Typ.)
	Brightness	380 cd/m ² (Typ.)
Video Input	VGA Signal	R/G/B Analog VGA/DVI(Optional)
	Scan Frequencies	"H:31.5~60 KHz V:56~75Hz"
Control	Power	On / Off with LED Indicator
Power Adaptor	Input	Universal AC 100~240 12V,4A, 50/60 Hz
	Output	DC 12V/ 3.0A
Power	Management	VESA DPMS Standard
	Consumption	35W Max. / Standby 2W max.
Environment	Temperature	0 °C~40 °C
	Humidity	10%~85%(20%~85% for MSR)
Safety & EMI		FCC-B, cETLus, CE, CCC, BSMI
Applications		POS, Banking, ATM, IPC, TML, WEB IA, Mini PC,..etc
Optional	Touch Panel	Resistive(5Wires)/USB and RS-232 interface
	Glass	Anti-Reflection Strengthen Glass
	MSR	RS232 or USB MSR
	Cabinet Color	White or Black

Dimension



unit: mm

*Specifications subject to change without notice.

TAIWAN VIDEO SYSTEM CO., LTD.

8F., No. 139, Zhengzhou Rd., Datong District, Taipei City 103, Taiwan
Tel:886-2-2553-6200 Fax:886-2-2553-6128 Email:info@tvs.com.tw http://www.tvs.com.tw